NAME

snp/snp – CUTEr interface with the SNOPT solver.

SYNOPSIS

[sd]snp [−decode] [−n] [−h] [−k] [−r] [−o *0|1*] [−l *secs*] [−f] [−b] [−a *1|2*] [−show] [[−param *name=value*[,*name=value...*]] [−force]] [−debug] [−L*path/to/lib*] [−−blas *keyword*] [−−lapack *keyword*] [*problem[.SIF]*]

DESCRIPTION

sdsnp interfaces the SNOPT solver with the CUTEr tools and SIF-encoded problems. *sdsnp* applies the SIF decoder to the problem *problem.SIF* to produce the OUTSDIF.d file and the problem-dependant Fortan subroutines. If *problem.SIF* has already been decoded, the script *snp* may be run by itself. SNOPT linearizes the nonlinear contributions to the objective and constraint function so that linear programming techniques can be exploited.

sdsnp is only included for backward compatibility with earlier versions of CUTE, and simply calls *snp* with the −*decode* flag.

snp sets the environment and calls *runpackage* to link all the needed libraries and modules for the SNOPT solver to solve the problem decoded from the SIF file and generates the executable.

[sd]snp Options

You can start [sd]snp with the following options:

−decode
Applies the SIF decoder to the problem *problem.SIF* to produce the OUTSDIF.d file and the problem-dependant Fortan subroutines. It is redundant to call *sdsnp* with the −decode flag.

−n Use the load module if it already exists. Compiling a new load module is the default.

−h Print a short help message.

−k Keep the generated executable after use. May be useful when solving a particular problem with the same solver with different parameters. Deleting the executable after use is the default.

−r Discourage recompilation of the test problem. Default is to recompile object files.

−o *0|1*
Regulates the output level of *[sd]snp*. Verbose mode is **-o** 1, silent mode is **-o** 0. Silent mode is the default.

−l *secs*
sets a limit of *secs* second on SNOPT runtime. Unlimited cputime is the default.

−f Use automatic differentiation in Forward mode

−b Use automatic differentiation in Backward mode

−a *1|2*
−a 1 uses the older HSL automatic differentiation package AD01 and −a 2 uses the newer HSL automatic differentiation package AD02. −a 2 is the default.

−show
displays possible parameter settings for problem[.SIF]. Other options are ignored.

−param
cast problem[.SIF] against explicit parameter settings. Several parameter settings may be given as a comma-separated list following −param or using several −param flags. Use *sifdec -show problem* to view possible settings. If a setting is not allowed in the SIF file, no action is taken unless −*force* is present.

−force
Forces the setting of the parameters named using −*param* to the given values, even if those values are not predefined in the SIF file.

−L*path/to/lib*
This option is passed directly to the linker and causes the path *path/to/lib* to be searched for libraries.

−−blas *keyword*
Overrides usage of the default *linpack* library packaged with CUTEr. Instead, use the BLAS library specified by *keyword*. The keyword *keyword* has one of two forms. The first, *-lmyblas* causes the linker to search for BLAS subprograms in the libmyblas.a library. The second, *none*, causes the linker to skip inclusion of any external BLAS. Use the first option if an optimized BLAS library is available on the host system, e.g., the ATLAS BLAS. The second option is useful for packages which already include the necessary BLAS subprograms.

−−lapack *keyword*
Overrides usage of the default *linpack* library packaged with CUTEr. Instead, use the LAPACK library specified by *keyword*. The keyword *keyword* has one of two forms. The first, *-lmylapack* causes the linker to search for LAPACK subroutines in the libmylapack.a library. The second, *none*, causes the linker to skip inclusion of any external LAPACK. Use the first option if an optimized LAPACK library is available on the host system. The second option is useful for packages which already include the necessary LAPACK subprograms.

problem
problem.SIF is the name of the file containing the SIF information on the problem to be solved.

ENVIRONMENT

CUTER
Home directory for CUTEr

MYCUTER
Home directory of the installed CUTEr distribution.

MASTSIF
A pointer to the directory containing the CUTEr problems collection. If this variable is not set, the current directory is searched for *problem.SIF*. If it is set, the current directory is searched first, and if *problem.SIF* is not found there, $MASTSIF is searched.

AUTHORS

A.R. Conn, N.I.M. Gould, D. Orban and Ph.L. Toint

NOTES

SNOPT is distributed by the Office of Technology Licensing at Stanford University and is subject to certain license agreements. SNOPT is authored by Philip Gill, Mike Saunders and Mike Gertz and is copyrighted by Stanford University.

SEE ALSO

CUTEr (and SifDec): A Constrained and Unconstrained Testing Environment, revisited,
N.I.M. Gould, D. Orban and Ph.L. Toint,
ACM TOMS, **29**:4, pp.373-394, 2003.

CUTE: Constrained and Unconstrained Testing Environment,
I. Bongartz, A.R. Conn, N.I.M. Gould and Ph.L. Toint,
TOMS, **21**:1, pp.123-160, 1995.

SNOPT 5.4 USER'S GUIDE,
Technical Report SOL xxx-xx, Department of Operations
Research, Stanford University, Stanford CA 94305, USA,
19xx.

sifdecode(1), gen(1).