NAME

UPROD − CUTEr tool to form the matrix-vector product of a vector with the Hessian matrix.

SYNOPSIS

CALL UPROD(N, GOTDER, X, P, Q)

DESCRIPTION

The UPROD subroutine forms the product of a vector with the Hessian matrix of the objective function of the problem decoded into OUTSDIF.d at the point X in the case where the only possible constraints are bound constraints.

ARGUMENTS

The arguments of UPROD are as follows

N [in] - integer
the number of variables for the problem,

GOTDER [in] - logical
a logical variable which specifies whether the first and second derivatives of the groups and elements have already been set (GOTDER = .TRUE.) or if they should be computed (GOTDER = .FALSE.),

X [in] - real/double precision
when GOTDER = .FALSE., the derivatives will be evaluated at X. Otherwise X is not used.

P [in] - real/double precision
an array which gives the vector whose product with the Hessian is required,

Q [out] - real/double precision
an array which gives the result of multiplying the Hessian by P.

NOTE

GOTDER should be set to .TRUE. whenever

(1)
a call has been made to UDH, USH, UGRDH or UGRSH at the current point, or

(2)
a previous call to UPROD, with GOTDER = .FALSE., at the current point has been made.

Otherwise, it should be set .FALSE.

AUTHORS

I. Bongartz, A.R. Conn, N.I.M. Gould, D. Orban and Ph.L. Toint

SEE ALSO

CUTEr (and SifDec): A Constrained and Unconstrained Testing Environment, revisited,
N.I.M. Gould, D. Orban and Ph.L. Toint,
ACM TOMS, **29**:4, pp.373-394, 2003.

CUTE: Constrained and Unconstrained Testing Environment, I. Bongartz, A.R. Conn, N.I.M. Gould and Ph.L. Toint, TOMS, **21**:1, pp.123-160, 1995.

cprod(3M).